

RH120/10 排水管



EN

Water discharge hose

Application:

softwall discharge hose for water, non corrosive fluids and compressed air; used in construction sites, industries and agriculture.

Temperature:

-35°C (-31°F) to +70°C (+158°F).

Construction:

Tube: black, smooth, synthetic rubber.

Reinforcement: high strength synthetic cord.

Cover: black, smooth, (wrapped finish) synthetic rubber, weathering and ozone resistant.

Also available upon request:

1.Different diameters 2.Yellow or blue hose cover 3.Different working pressures.

CN

排水管

应用范围:

适用于水或不具腐蚀性的液体和压缩空气；适用于建筑工地，工业和农业领域等

温度范围:

-35°C(-31°F) 到 +70°C(+158°F)

软管结构:

内层: 黑色, 光滑, 合成橡胶

加强层: 高强度合成线绳

外层: 黑色, 光滑, 合成橡胶, 耐侵蚀, 耐氧化

可选择项:

1. 不同口径 2. 黄色或蓝色外层 3. 各种工作压力

产品型号 code	内径 inside diameter		外径 outside diameter	工作压力 working pressure	爆破压力 burst pressure	重量 weight nominal	长度length
RH120	(in)	(mm)	(mm)	(bar)	(bar)	(kg/m)	(m)
RH120-12	3/4	19	26	10	30	0.30	60
RH120-16	1	25	33	10	30	0.47	60
RH120-20	1-1/4	32	42	10	30	0.79	60
RH120-24	1-1/2	38	47	10	30	0.79	60
RH120-32	2	51	61	10	30	1.14	60
RH120-40	2-1/2	63.5	75.5	10	30	1.74	60
RH120-48	3	76	87	10	30	1.82	60
RH120-56	3-1/2	90	106	10	30	3.18	60
RH120-64	4	102	120	10	30	4.14	60